


SL26 83" LL

All dimensions are measured in inches and [millimeters] from the top of the door to the centerline of the holes and ATW panels.

Choose location for ATW prep. ATW4 = 1 location; ATW8 = 1 location; and ATW12 = 1 location.

NOTE: All unspecified angles default to 90°. To avoid an upcharge, 180° openings must be clearly specified at the time of order. There will be an upcharge for 180° ATW cover plates when ordered separately and finish (Clear, Bronze or Black) must be specified.

SL26 Profile



52 fasteners / 32 bearings

HOLES	ATW LOCATIONS
1 1/2 [38.1]	0 [0]
3 1/2 [88.9]	
5 1/2 [139.7]	
	8 3/16 [208.0]
10 [254.0]	
15 [381.0]	13 5/16 [338.1]
20 [508.0]	18 7/16 [468.3]
25 [635.0]	23 9/16 [598.5]
30 [762.0]	
34 [863.6]	36 3/8 [923.9]
	38 15/16 [989.0]
41 1/2 [1054.1]	
	44 1/16 [1119.2]
49 [1244.6]	46 5/8 [1184.3]
53 [1346.2]	
58 [1473.2]	59 7/16 [1509.7]
63 [1600.2]	64 9/16 [1639.9]
68 [1727.2]	69 11/16 [1770.1]
73 [1854.2]	74 13/16 [1900.2]
77 1/2 [1968.5]	
79 1/2 [2019.3]	
81 1/2 [2070.1]	
	83 [2108.2]